

TR-4 SYNTHETIC BLEND RACING OILS

SAE: 20W-50, 25W-60

>>Description

TR-4 Synthetic Blend Racing Oils are specifically formulated for racing engines using alternative fuels, superchargers, turbo chargers or nitrous oxide systems. The unique blend of synthetic and hydro processed petroleum base stocks provide exceptional thermal stability and superior ring sealing capabilities under the most severe conditions.. TR-4 incorporates a unique combination of race specific additives and polymers designed to reduce wear, eliminate deposits and maintain optimum oil pressure. TR-4 also utilizes our MPZ chemistry which reduces frictional losses for increased horsepower and torque.

>>Features

- >Synthetic blend formula
- >For alternative fuels, superchargers, turbo chargers or nitrous systems
- >Exceptional thermal stability & ring seal
- >Superior wear and deposit control chemistry
- >Formulated with MPZ for decreasing frictional losses

>>Application

SAE 20W50 - recommended for use in racing engines or highly modified street engines where an SAE 15W50 or 20W50 are specified. Highly recommended for gas or alcohol fuels. This includes aspirated, injected, supercharged, turbo charged or nitrous oxide equipped applications. Commonly used in sprint cars, drag racing and circle track. Maximizes ring sealing.

SAE 25W60 - Recommended for use in larger displacement (big bore) racing engines or highly modified street engines where an SAE 20W60, 25W60, 50 or 60 are specified. Highly recommended for full or partial alcohol fuels. This includes aspirated, injected, supercharged, turbo charged or nitrous oxide applications. Also recommended for injected engines using full or partial blends of nitro methane. Maximizes ring sealing.

TR-4 is formulated to Torco's proprietary race specific additive technology.

Exceeds API performance requirements. Intended for racing applications.

>>Typical/Test Data

SAE Grade	20W-50	25W-60
Viscosity @ 100°C	21.4	24.5
Viscosity @ 40°C	107.5	192
Pour Point °C	-28	-26
Flash Point °C	224	230
Appearance	Amber	Amber

>>Directions

Follow manufacturer's fill level requirements.

Compatible with other petroleum and synthetic lubricants.

>>Package Sizes / P/N

SAE Grade:	20W50	25W60
1 Liter (1.056 US QT)	A172050CE	A172560CE
Case 12 Liters	A172050C	A172560C
5 Gallon Pails	A172050E	A172560E
55 Gallon Drum	A172050B	A172560B

